



Effective March 3, 2011, new **Child Safety Standards** (ANSI/WCMA 1/A100.1-2010) must be implemented. The new standard impacts Insolroll shades with manual clutch and continuous bead chain operators. It requires that a compliant chain tension device be utilized on every shade and that the device renders the shade partially inoperable when not properly installed. The new standard also includes new **Safety Labeling Requirements**.

## Insolroll offers 3 locking chain guide choices that meet the new tension device safety standard.


### METAL SELECT

#### Locking Chain Guide

Available in Black, White & Nickel

Direct mount

Our exclusive and elegant metal chain guide tensioner—designed with safety and style in mind.



Available colors, left to right:

Antique Brass, Nickel, White, Brown & Black

### UNIVERSAL


#### Locking Chain Guide

Available in Black & White (shown)

Direct mount

Designed with an auto-locking mechanism that renders shade inoperable if bracket comes loose from the wall

2 3/4"



### SPRING-TITE

#### Locking Chain Guide

Available in Black & White

Direct mount

3"



Wall mount bracket



Partial inside mount bracket



**✓ New Bead Chain Style**


We have converted from a single-ball, double-spaced polyester bead chain to a double-ball, single-space bead chain. This enhancement provides a smoother, easier pull as the chain glides through the clutch and chain guide. Available in polyester black, polyester brown, polyester white, metal nickel and metal antique brass.



Poly Black Poly Brown Poly White Metal Nickel Metal Antique Brass

**✓ New Safety Labeling Requirements**

All manually operated shades will now have a Safety Label designed to match the new ANSI/WCMA standards. The new standard requires permanent labeling, advising of the product's potential hazards and specifying product origin. (Name, City, State and Year of Manufacture).



**Generic Warning Bottom Rail Labels**

**5.1.1** ...The label shall be permanently affixed to all products with accessible cords. The label shall be placed on the bottom rail of the blind, and printed in a color that contrasts the bottom rail color...



**✓ How Your Shades Will be Shipped**

When you receive your shades, the chain guide will be attached to the chain and locked in place *rendering the shade inoperable until the chain guide is properly installed.*

**✓ Installer Responsibility**

The new standard requires installers to install locking chain guides on EVERY window treatment with a continuous cord loop.

**Specific changes to the new standards that affect Insolroll shades with manual clutch operators.**

**Tension Devices for window coverings with cord or bead loops shall adhere to the following:**

- 6.5.1** The tension device shall be attached to the cord or bead loop by the manufacturer. It shall be designed, placed and shipped such that, unless properly installed or altered from the shipped condition with sequential process or tools, it prevents the window covering from operating.
- 6.5.2** The tension device shall be designed so when not properly installed will, at least partially, prevent the lift system from moving the window covering through lowering and raising.



\* For a read-only copy of the new standard, visit this web page: <http://windowcoveringsassociationofamerica.org/>